


Data Cable, Cat6A, F/FTP, 23AWG, LSZH - FC6AFFLW



DESCRIPTION

FABNET Category 6A shielded twisted pair (F/FTP) cables are constructed with a 4 x 2 x 23 AWG copper wire structure to Class EA standards and to support protocols up to 500 MHz. F/FTP cables are excelled in environments prone to heavy external interference like EMI, ensuring uninterrupted signal transmission. This cable uses a 5-foil screened design consisting of 4 individual foils wrapped in pairs plus an overall foil shield. Supports channel performance exceeding ANSI/TIA and ISO/IEC Category6A requirements.

APPLICATIONS

- Supports category 6A networks running up to 500MHz applications.
- 100BASE-T through 10GBASE-T Ethernet
- Power over Ethernet (PoE)- IEEE 802.3bt Type 1 to 4
- Horizontal and backbone in structured cabling installations

SPECIFICATIONS & FEATURES

- The cable shall meet ISO/IEC11801, ANSI/TIA-568.2-D, EN50173
- Outer Jacket: LSZH
- 23AWG premium grade copper conductor
- F/FTP cable structure for better shielding in external interference environments

MECHANICAL & PHYSICAL PROPERTIES

Basic Conductor	Solid Bare Copper	Category	CAT 6A F/FTP
Conductor Size	23 AWG	Insulation Material	Skin-foam-skin PE
Insulation Material	Skin-foam-skin PE	Insulation Diameter	1.330±0.1mm
Number of Insulated Conductors	8, twisted in 4 pairs	Screening	Al/Mylar
Color Code of Pairs	1 White- Blue /Blue 2 White-Orange /Orange 3 White-Green /Green 4 White- Brown /Brown	Sheath Material	LSZH
Sheath Thickness	0.55±0.15 mm	Sheath Surface	Clean,Frap,Satiation
Jacket Color	White. Other colors available upon request	Operating Temperature	-40 to +70C

ELECTRICAL SPECIFICATIONS

Characteristic Impedance	100±15 Ohm @ 1-500 MHz
DC Resistance	< 9.38 Ω / 100m
Resistance unbalance	5% Max
Capacitance	56 pF/m nom. @ 1 KHz
Cap. Unbalance (wire to ground)	1600 pF/Km max. @ 1 KHz
Voltage rating	72 Vdc max.
Dielectric strength	1.7 KV A.C/2 Seconds
Velocity of Propagation (NVP)	74%
Propagation delay	534 + 36/f½ nS/100m max @ 1-500 MHz
Propagation Delay Skew	45 nS/100m max @ 1-500 MHz
Insulation Resistance	5000 MegaOhm·Km min. @ 500 Vdc
Coupling attenuation	55 dB min @ 30-100 MHz 55-20Log(f/100) @100-500 MHz

PACKING DETAILS

Length (Mtr)	Approx. OD(mm)	Packaging Type
305	7.5±0.8 mm	REEL
500	7.5±0.8 mm	REEL

ORDERING INFORMATION

FC6AFFLW-AT	Data Cable, Cat6A, F/FTP, 23AWG, LSZH, White, 305 Mtr
FC6AFFLW-AF	Data Cable, Cat6A, F/FTP, 23AWG, LSZH, White, 500 Mtr

*Jacket Colour Variants (W-White, B-Blue, G-Gray, C-Customized)